

Fall Winter 25/26 | Stock Service Tejido Industrial | Essentials | Alpawool Light - Woolen Spun

ALPAWOOL LIGHT - WOOLEN SPUN







INDUSTRIAL FINISHING

4908

6085

0310

0574

- Machine wash, using wool cycle and low speed. To avoid felting, temperature should not exceed 45°C * 9 - minute wash cycle. Rapid impeller movements for 15 seconds followed by 5-second rest periods. After centrifugation, dry at 80°C. Note: Do not overload the machine with garment pieces.

8145

1800

COLORS AVAILABLE

Refer to Stock Service Color Card



	COLOR FASTNESS (AVERAGE VALUES)			
	Dry rubbing	Wet rubbing	Wash fastness	
Light	4	4	4	
Medium	4	3	4	
Dark	3	2/3	3	

TECHNICAL INFORMATION	KETTLE SIZE (Kg.)	SUGGESTED GAUGE	CERTIFICATION
Dyeing method Hanks/Tops Knot type Splicer Pilling 3	Hanks Tops 30 150 40 80 250	799	CONTIDENCE IN TEXTILES STANDARD 100 16.HPE.22779 HONENSTEIN HTTI Tested for Familia substances. www.oeko-tex.com/standard/100

NOTES:

- Might occur bleeding in design with white stripes and intense colors.
- Consult our sales team about dyeing process that decrease bleeding risk on intense colors.
- Minimum for dark colors subject to revision.