

Fall Winter 25/26 | Stock Service Tejido Industrial | Essentials | Kid Silk

KID SILK



72% Kid Mohair (28 mic.) / 28% Mulberry Silk

NM 1/8.4

W663

W660

W664

W666

W676

W658

W674 W662 W675







INDUSTRIAL FINISHING

- We recommend washing at 35° in gentle cycle during 3 minutes using a softener that does not exceed 4% of the weight of the material considering the finishing expected. Centrifuge for 2 minutes. Dry. Use manual iron. If a more pronounced pile is required, washing time or washing cycle revolutions should be increased, but the bath temperature must be reduced to avoid the felting effect.

COLORS AVAILABLE

Refer to Stock Service Color Card

CARE INSTRUCTION



Any solvent except tetrachiorethylene







COLOR FASTNESS (AVERAGE VALUES)

	Dry rubbing	Wet rubbing	Wash fastness
Light	4	3	4
Medium	4	3	3/4
Dark	3	2/3	3

TECHNICA INFORMATIO		KETTLE SIZE (Kg.)
Dyeing method Knot type Pilling	Hanks Knot 3.5	30 40 80 200

SUGGESTED GAUGE

 $7gg \sim 10gg$

CERTIFICATION **OEKO-TEX**® STANDARD 100
16.HPE.92779 HOHENSTEIN HTTI Tested for harmful substances. www.oeko-tex.com/standard100

NOTES:

- Might occur bleeding in design with white stripes and intense colors.
- Consult our sales team about dyeing process that decrease bleeding risk on intense colors.
- Minimum for dark colors subject to revision.