

Fall Winter 25/26 | Stock Service Tejido Industrial | Essentials | Suri Air (New)

SURI AIR (NEW)



NM 1/9.4

Color Card

7937

77F9

7V84

77G0







INDUSTRIAL FINISHING

- We recommend washing at 35° in gentle cycle during 3 minutes using a softener that does not exceed 4% of the weight of the material considering the finishing expected. Centrifuge for 2 minutes. Dry. Use manual iron. If a more pronounced pile is required, washing time or washing cycle revolutions should be increased, but the bath temperature must be reduced to avoid the felting effect.

COLORS AVAILABLE

Refer to Stock Service Color Card









CARE INSTRUCTION





COLOR FASTNESS (AVERAGE VALUES)

	Dry rubbing	Wet rubbing	Wash fastness
Light	4	3/4	4
Medium	3/4	2/3	3/4
Dark	3	2/3	3

TECHNICAL INFORMATION

Dyeing method Tops Knot Knot type Pilling

KETTLE SIZE (Kg.) 50 100

200

SUGGESTED GAUGE

3gg

CERTIFICATION **OEKO-TEX**® STANDARD 100 16.HPE.92779 HOHENSTEIN HTTI

NOTES:

- . Might occur bleeding in design with white stripes and intense colors.
- Consult our sales team about dyeing process that decrease bleeding risk on intense colors.
- Minimum for dark colors subject to revision.